

How can I draw arrows in ggplot2?

Authored by
stats writer

June 25, 2024

RECOMMENDED CITATION

stats writer (2024). *How can I draw arrows in ggplot2?*. PSYCHOLOGICAL SCALES.
Retrieved from <https://scales.arabpsychology.com/?p=152792>

Drawing arrows in ggplot2 is a useful tool for visualizing relationships and highlighting specific data points in a plot. To draw arrows in ggplot2, one can use the `geom_curve()` function and specify the x and y coordinates for the starting and ending points of the arrow. Additionally, the angle and curvature of the arrow can be adjusted to suit the specific needs of the plot. This feature allows for the creation of informative and visually appealing graphs in ggplot2.

Draw Arrows in ggplot2 (With Examples)

You can use the following basic syntax to draw an arrow in a plot in ggplot2:

```
library(ggplot2)
```

```
ggplot(df, aes(x=x, y=y)) +  
geom_point() +  
geom_segment(aes(x=5, y=6, xend=8, yend=9), arrow =  
arrow(length=unit(0.5, 'cm')))
```

Here is what each argument does in the `geom_segment()` function:

x: The x-value to start at
y: The y-value to start at
xend: The x-value to end at
yend: The y-value to end at
arrow: The length of the arrow head

The following example shows how to draw an arrow using ggplot2 in practice.

Example: Draw Arrows in ggplot2

Suppose we have the following data frame that contains information on the number of points scored and rebounds collected by various basketball players:

```
#create data frame
```

```
df <- data.frame(points=c(3, 3, 5, 6, 7, 8, 9, 9, 8, 5),  
rebounds=c(2, 6, 5, 5, 8, 5, 9, 9, 8, 6))
```

```
#view data frame
```

```
df
```

```
points rebounds
```

```
1 3 2
```

```
2 3 6
```

```
3 5 5
```

```
4 6 5
```

```
5 7 8
```

```
6 8 5
```

```
7 9 9
```

```
8 9 9
```

```
9 8 8
```


```
10 5 6
```

We can use the following syntax to create a scatter plot in ggplot2 and add an arrow to specific location on the plot:

```
library(ggplot2)
```

```
#create scatterplot and add arrow
```

```
ggplot(df, aes(x=points, y=rebounds)) +  
geom_point() +  
geom_segment(aes(x=5, y=6, xend=8, yend=9), arrow =  
arrow(length=unit(.5, 'cm')))
```



Feel free to modify the value in the `arrow()` function to increase or decrease the size of the arrow head.

For example, the following code shows how to increase the size:


```
library(ggplot2)
```

```
#create scatterplot and add arrow with increased arrow  
head size
```

```
ggplot(df, aes(x=points, y=rebounds)) +
```

```
geom_point() +
```

```
geom_segment(aes(x=5, y=6, xend=8, yend=9), arrow =  
arrow(length=unit(2, 'cm')))
```



You can also use the `color` and `lwd` arguments to change the color and line width of the arrow, respectively:

```
library(ggplot2)
```


```
#create scatterplot and add customized arrow
```

```
ggplot(df, aes(x=points, y=rebounds)) +
```

```
geom_point() +
```

```
geom_segment(aes(x=5, y=6, xend=8, yend=9), arrow =  
arrow(length=unit(.5, 'cm'))),
```

color='red', lwd=3)



Feel free to play around with the various arguments in the `geom_segment()` function to create an arrow that looks exactly how you'd like.

The following tutorials explain how to perform other common tasks in ggplot2: