How to Sort Bars in a Google Sheets Bar Chart

Authored by

stats writer

January 15, 2026

ARABPSYCHOLOGY.COM

RECOMMENDED CITATION

stats writer (2026). *How to Sort Bars in a Google Sheets Bar Chart*. PSYCHOLOGICAL SCALES. Retrieved from https://scales.arabpsychology.com/?p=126238

To effectively sort bars in a bar chart using Google Sheets, relying solely on the chart editor's basic settings often proves insufficient, especially when dealing with dynamic data. While you can use the traditional "Sort Range" feature found under the Data tab, this method permanently alters your source data, which is often undesirable for complex analytical projects. A superior, non-destructive approach involves leveraging the powerful built-in spreadsheet function: the SORT function. This technique allows you to create a completely new, sorted dataset in a separate range, from which you then generate your finalized visualization. This strategy ensures your original raw data remains intact while providing highly flexible control over your data visualization output, enabling quick and easy organization of metrics for better comparative analysis.

The Critical Role of Sorting in Data Visualization

In the realm of data analysis, the manner in which information is presented holds as much weight as the information itself. When constructing a bar chart, the arrangement of categories--whether alphabetical, chronological, or based on magnitude--fundamentally impacts the audience's ability to interpret the findings swiftly and accurately. A poorly organized chart forces the viewer to spend unnecessary effort comparing individual bars, detracting from the central message the data is meant to convey. Conversely, when bars are consistently sorted, often by value, patterns, outliers, and relative differences become immediately apparent, significantly enhancing the efficacy of the data visualization.

Google Sheets offers robust charting capabilities, but achieving a specific sorting order requires a strategic approach that goes beyond simple point-and-click customization. The primary goal is often to sort the bars in either ascending (smallest to largest) or descending (largest to smallest) order based on their numerical values. This critical organization step transforms a mere collection of data points into a powerful comparative tool. Understanding how to manage the underlying dataset using programmatic functions, specifically the **SORT** function, is key to producing dynamic and professional-grade visualizations within the spreadsheet environment.

Understanding the Default Chart Ordering Challenge

When you initially create a bar chart in Google Sheets, the chart inherits the order of the categories exactly as they appear in the source data range. If your source data is ordered alphabetically by region name, your chart will reflect that alphabetical order, regardless of the corresponding sales figures. This default setting is logical but often counterproductive for visual analysis, especially if the data is substantial or complex. For example, if a spreadsheet lists regions A, C, B, and D in that specific sequence, the chart will display them in that order. If Region C has the highest sales, placing it in the middle of the chart can obscure its prominence as an outlier or top performer.

To ensure that the most important metric (like the highest sales) is visually prioritized--usually by

ARABPSYCHOLOGY.COM

placing it at the top or bottom of the chart--we must first restructure the data feeding the chart. This crucial step involves creating a temporary helper range that contains the data sorted according to the desired metric, without disturbing the original source table. This preservation of the original data integrity while creating a sorted view is paramount in advanced spreadsheet management, ensuring traceability and reducing the risk of data corruption.

The Solution: Leveraging the SORT Function

This required restructuring is efficiently accomplished using the built-in SORT function in Google Sheets. The SORT function is an array formula designed to sort the rows of a given array or range by the values in one or more specified columns. Crucially, it returns the sorted results as a new, temporary array, leaving the original source data completely untouched. This non-destructive capability makes it the ideal tool for generating sorted visualizations that are both accurate and dynamic.

The core syntax for the SORT function requires three primary, sequential arguments, which dictate precisely how the sorting operation is executed:

Range (A2:B7): This defines the entire source dataset--both the category labels and the values--that needs to be sorted.
Sort Column Index (2): This numerical argument specifies which column within the defined range contains the values we wish to sort by. If the values are in the second column of the selected range, the index is 2.
Is Ascending (TRUE or FALSE): This boolean value determines the direction of the sort. **TRUE** signifies ascending order (A-Z, smallest to largest), while **FALSE** signifies descending order (Z-A, largest to smallest).

By carefully defining these parameters, we can generate a temporary, dynamically updated data table that serves as the perfect foundation for our organized bar chart.

Step-by-Step Implementation: Initial Dataset Preparation

To illustrate this technique, we begin by defining a sample dataset representing company sales across various geographical regions. We assume this raw data is stored in columns A and B of your spreadsheet.

First, establish the following base data, ensuring region names are in Column A and corresponding sales figures are in Column B (cells A2 through B7):


ARABPSYCHOLOGY.COM

	A	B	C	D
1	**Region**	**Sales**		
2	North	25		
3	East	49		
4	South	22		
5	West	27		
6	Central	41		
7	Pacific	33		
8				
9				
10				
11				
12				
13				
14				
15				

ARABPSYCHOLOGY.COM

Next, to observe the default behavior, create the initial bar chart. Highlight the cell range **A2:B7**, navigate to the **Insert** tab, and click **Chart**. The resulting visualization will display the sales data for each region in the exact unsorted sequence they appeared in the dataset. As shown below, this default ordering often hinders rapid comparative analysis:

	A	B	C	D	E	F
1	**Region**	**Sales**				
2	North	25				
3	East	49				
4	South	22				
5	West	27				
6	Central	41				
7	Pacific	33				



Sorting the Bar Chart in Ascending Order

If the analytical requirement is to arrange the bars from the lowest sales figures up to the highest sales figures, signifying an ascending sort, we must utilize the **TRUE** argument within the SORT function. This is highly useful for identifying underperforming categories or visualizing a distribution curve starting from the baseline.

Select an empty cell, such as **D2**, to host the sorted dataset. Enter the following array formula:

=SORT(A2:B7, 2, TRUE)

Upon execution, the formula dynamically populates cells D2 through E7 with the regions and their sales figures, rearranged according to the sales values from smallest to largest. The argument 2 specifies sorting by the Sales column, and TRUE confirms the ascending order.

ARABPSYCHOLOGY.COM


D2 =SORT(A2:B7, 2, TRUE)

	A	B	C	D	E
1	**Region**	**Sales**			
2	North	25		South	22
3	East	49		North	25
4	South	22		West	27
5	West	27		Pacific	33
6	Central	41		Central	41
7	Pacific	33		East	49
8					
9					
10					
11					
12					

Finally, highlight this newly generated sorted range (**D2:E7**), click the **Insert** tab, and then **Chart**. The resulting visualization is now an organized bar chart that clearly presents the performance hierarchy, sorted from smallest to largest sales.

ARABPSYCHOLOGY.COM

	A	B	C	D	E	F	G
1	**Region**	**Sales**					
2	North	25		South	22		
3	East	49		North	25		
4	South	22		West	27		
5	West	27		Pacific	33		
6	Central	41		Central	41		
7	Pacific	33		East	49		



Sorting the Bar Chart in Descending Order

For reports where the immediate focus must be on the top performers or largest figures, a descending sort order is essential. This arrangement places the largest values prominently, which is standard practice in executive dashboards and high-level performance reviews.

To achieve this descending sort, we must instruct the SORT function to use **FALSE** as its third argument. This boolean value signals the spreadsheet to arrange the data from highest to lowest. We will again place this formula in cell **D2**, assuming we overwrite the previous ascending formula:

=SORT(A2:B7, 2, FALSE)

Executing this formula generates a new array in the D2:E7 range, listing the regions in descending order based on their sales figures. The argument FALSE specifies that we'd like to sort the values in descending order, ensuring the highest values are listed first.

ARABPSYCHOLOGY.COM


D2 =SORT(A2:B7, 2, FALSE)

	A	B	C	D	E
1	**Region**	**Sales**			
2	North	25		East	49
3	East	49		Central	41
4	South	22		Pacific	33
5	West	27		West	27
6	Central	41		North	25
7	Pacific	33		South	22
8					
9					
10					
11					
12					
13					

Once the new array is calculated, highlight the cell range **D2:E7**, then click the **Insert** tab along the top ribbon, and click **Chart**. The resulting bar chart will now visually display the ranking of sales from largest to smallest, providing immediate visual impact and clarity regarding peak performance.

ARABPSYCHOLOGY.COM

	A	B	C	D	E	F	G
1	**Region**	**Sales**					
2	North	25		East	49		
3	East	49		Central	41		
4	South	22		Pacific	33		
5	West	27		West	27		
6	Central	41		North	25		
7	Pacific	33		South	22		



ARABPSYCHOLOGY.COM

Benefits of Using Array Formulas for Dynamic Visualization

The core strength of using an array formula like SORT function for chart generation lies in its innate dynamic nature. Unlike manual sorting of the source data, the formula automatically updates the sorted range and the dependent chart whenever the underlying values in the original range (A2:B7) change. If a new data entry dramatically shifts a region's rank, the output chart adjusts instantly, making this method ideal for live dashboards and frequently updated analytical reports.

This dynamic approach prevents the need for repetitive manual sorting and chart recreation, saving significant time and reducing the possibility of human error. It enforces a clean separation between the raw data input and the manipulated visual output, which is a best practice in robust data management. For complete technical reference on all parameters and capabilities of this essential tool, refer to the official SORT function documentation provided by Google.

Related Google Sheets Tutorials

The following tutorials explain how to perform other common and highly useful data manipulation and data visualization tasks in Google Sheets:

Understanding Array Formulas in Google Sheets for Advanced Calculations
Creating Dynamic Ranges using the FILTER Function
Implementing Conditional Formatting for Data Highlights and Outliers

ARABPSYCHOLOGY.COM