

How to add a footnote to ggplot2 plots?

Authored by
stats writer

November 21, 2025

RECOMMENDED CITATION

stats writer (2025). *How to add a footnote to ggplot2 plots?*. PSYCHOLOGICAL SCALES.
Retrieved from <https://scales.arabpsychology.com/?p=98706>

Effective data visualization often requires providing supplementary information to ensure the audience fully understands the context of the displayed data. This extra detail, commonly presented as a footnote or caption, is crucial for citing sources, explaining data limitations, or clarifying complex methodologies. While earlier methods might have relied on functions like `annotate()`, the standard and most robust approach within the powerful `ggplot2` framework for adding such text is by leveraging the `caption` argument inside the `labs()` function.

The `annotate()` function is extremely versatile and allows developers to place text or graphical elements anywhere on the plot space using specific coordinates. However, for standard metadata like source citations or explanatory notes placed consistently below the plot area, using the dedicated `caption` argument is preferred. This method ensures the footnote is correctly positioned relative to the plot panel and maintains compatibility with various themes and resizing operations, adhering to the principles of the `ggplot2` Grammar of Graphics.

This comprehensive guide details exactly how to implement captions or footnotes in your `ggplot2` visualizations, focusing on the straightforward application of the `labs()` function and subsequent customization of its alignment using the `theme()` function. Mastering these tools ensures that your visualizations are not only aesthetically pleasing but also fully documented and contextually rich.

The Role of ggplot2 in R

The `ggplot2` package is an essential component of the Tidyverse collection in the `R` programming environment. It is renowned for implementing the Grammar of Graphics, a powerful conceptual framework that allows users to build plots layer by layer. This systematic approach enhances the clarity and reproducibility of data visualization, making it the preferred tool for countless analysts and scientists globally. Every element of a `ggplot2` plot--from the underlying data to the geometric shapes, scales, and labels--is treated as a distinct layer that can be individually controlled.

When creating a complex visualization, it is vital to manage metadata effectively. Metadata often includes the title, axis labels, and critically, the caption or footnote. These elements are handled primarily through the `labs()` function, which acts as a central hub for defining all textual descriptions associated with the plot. Using a standardized function like this ensures consistency across different types of plots and simplifies the process of making the visualization self-explanatory.

Understanding how the plot components interact is key to advanced customization. The footnote, once added via `labs(caption)`, is treated as a plot element that resides within the overall plot region but outside the main plotting panel. Its position and styling are governed by the overarching plot theme, which is modified using the powerful `theme()` function. This hierarchical structure allows for precise control over the footnote's appearance, including its font, size, color, and alignment, which we will explore in detail.

Primary Method: Utilizing the labs() Function for Captions

The most straightforward and highly recommended way to add a footnote in `ggplot2` is by using the `caption` argument within the `labs()` function. The `labs()` function is designed specifically for setting plot labels, including the title, subtitle, axis labels (x and y), and the caption. By default, the text assigned to the `caption` argument appears in the bottom-right corner of the visualization, positioned below the primary plotting area.

To integrate a footnote, you must pass the desired text string to the **caption** argument inside the **labs()** function. This is typically appended to the main plot object using the addition operator (+).

There are two key approaches when applying this argument, depending on the required alignment:

Method 1: Default Alignment (Bottom Right Corner)

This method utilizes the default settings of `ggplot2`, placing the footnote on the right side. This is often suitable for source citations.

```
p +  
labs(caption = "Data Source: Internal Study, Q4 2023.")
```

Method 2: Custom Alignment (Bottom Left Corner)

If you require the footnote to be aligned to the left, which is standard for explanatory notes or copyright statements, you must combine `labs()` with the `theme()` function to override the default alignment parameter.

```
p +  
labs(caption = "Note: Data restricted to subjects aged 18-65.") +  
theme(plot.caption = element_text(hjust=0))
```

We will now demonstrate both methods using a simple `R data frame`, illustrating the practical application of these code snippets in a complete visualization workflow.

Data Preparation and Setup for Demonstrations

Before diving into the visualization code, it is essential to establish the data structure that will be used across all examples. We will create a simple `data frame` in `R` containing two variables: `assists` and `points`. This dataset is small enough to be easily inspected and perfect for generating a clear `scatter plot`.

The `data frame` structure is fundamental in `R`, organizing data into rows and columns, similar to a spreadsheet. For our demonstration, we map `assists` to the X-axis and `points` to the Y-axis, investigating the potential relationship between these two numerical variables. This setup is standard practice when initiating any data analysis or visualization project using `ggplot2`.

The following code initializes the data frame named `df` and displays its contents. Note that the structure of the data itself does not influence the footnote placement; rather, it provides the necessary foundation upon which the plot is built.

```
# Create the demonstration data frame named df  
df <- data.frame(assists=c(1, 2, 2, 3, 5, 6, 7, 8, 8),  
points=c(3, 6, 9, 14, 20, 23, 16, 19, 26))
```

```
# View the data frame structure and contents  
df
```

```
assists points
```

```
1 1 3
```

```
2 2 6
```

```
3 2 9
```

```
4 3 14
```

```
5 5 20
```

```
6 6 23
```

```
7 7 16
```

```
8 8 19
```

```
9 8 26
```

Example 1: Default Placement (Bottom Right Alignment)

In this first example, we utilize the standard implementation of the `caption` argument to add a footnote. By default, `ggplot2` right-aligns the caption text relative to the overall plot boundaries. This alignment is suitable for citing data sources or providing brief acknowledgments that are typically expected in the lower right corner of a figure.


We begin by loading the necessary `ggplot2` library. We then construct a basic `scatter plot`, mapping the `assists` and `points` variables to the respective axes using the `aes()` function, and specifying the use of points via `geom_point()`. The final step is chaining the `labs()` function, defining our footnote text within the `caption` argument.

Observe how the code structure adheres to the layered approach of the Grammar of Graphics: defining the data and mappings first, adding the geometric shapes (points) second, and finally

applying labels and annotations. This systematic process ensures that all elements of the visualization are built logically and reproducibly.

library(ggplot2)

```
# Create scatter plot with footnote using default (bottom right) alignment
ggplot(df, aes(x=assists, y=points)) +
  geom_point(size=3) +
  labs(caption = "Source: Simulated Athlete Performance Data 2024.")
```



As demonstrated in the resulting figure, the descriptive text has been successfully added to the bottom right area of the chart. This default positioning is achieved without requiring any complex theme modifications, making it the simplest implementation for adding explanatory text.

Customizing Footnote Position with `theme()` and `element_text()`

While the default right alignment is often acceptable, researchers frequently need to align captions to the left (e.g., for formal reporting standards) or center them (e.g., when the footnote is very short or stylized). To achieve precise control over the footnote's position and appearance, we must utilize the comprehensive styling capabilities provided by the `theme()` function.

The `theme()` function allows modification of non-data components of the plot, such as background colors, fonts, and the positioning of titles and captions. Specifically, we target the `plot.caption` element, which controls the aesthetics of the text defined by `labs()(caption)`. To change the appearance, `plot.caption` must be assigned an output from the `element_text()` helper function.

The critical parameter within `element_text()` for horizontal alignment is `hjust`. This argument takes a numerical value between 0 and 1, where 0 represents left alignment, 0.5 represents center alignment, and 1 represents right alignment. By setting `hjust=0`, we instruct R to position the start of the caption flush with the left edge of the overall plot region.

Example 2: Left Alignment Using `hjust=0`


For scenarios where the footnote needs to be left-aligned--a common requirement when the caption is longer or when adhering to specific document formatting--we incorporate the `theme()` customization layer. This method extends the code from Example 1 by adding one crucial line that overrides the default alignment settings.

The process starts identically to the first example: loading the library, defining the data mappings, and specifying the geometric elements. The distinction arises when appending the `theme()` function after `labs()`. Inside `theme()`, we target `plot.caption` and set it equal to `element_text(hjust=0)`. This explicit specification forces the caption to be left-aligned.

It is important to remember that the `hjust` parameter controls the horizontal justification (alignment) relative to the plot area. A value of 0 signifies the alignment anchor is on the left edge. If you omit the `theme()` call entirely, `ggplot2` defaults internally to a value of `hjust=1`, resulting in the right alignment seen in Example 1.

library(ggplot2)

```
# Create scatter plot with footnote in bottom left corner using theme() modification
ggplot(df, aes(x=assists, y=points)) +
  geom_point(size=3) +
  labs(caption = "This data represents aggregated, anonymized athlete scores.") +
  theme(plot.caption = element_text(hjust=0))
```



The resulting plot clearly shows the footnote text positioned on the far left side, underneath the Y-axis label. This fine-tuning provides flexibility necessary for professional data visualization and report generation, ensuring complete control over the final presentation.

Advanced Alignment Options for Footnotes

Beyond the common left (0) and right (1) alignment options, the `hjust` parameter offers full continuous control over the horizontal positioning of the footnote. This flexibility allows for scenarios such as centering the caption beneath the plot or offsetting it slightly for stylistic reasons. Understanding the `hjust` scale is crucial for mastering detailed customization in `ggplot2`.

To center the footnote, you simply set `hjust=0.5` within the `element_text()` function. This centers the caption horizontally relative to the total plot width, effectively placing it underneath the center of the plotting panel and potentially bridging the space between the X and Y axes labels. This is often an excellent choice when the footnote is brief and serves as a generalized note rather than a specific source citation.

Furthermore, you can also manipulate the vertical positioning (using `vjust`, although less commonly needed for footnotes) and the visual styling, such as font size, color, and face (bold, italic). For example, to make a centered footnote smaller and italicized, you would use:

```
p +  
labs(caption = "Centered and Styled Note.") +  
theme(plot.caption = element_text(hjust=0.5, size=8, face="italic"))
```

These advanced options highlight the power of the `theme()` system in `ggplot2`, ensuring that the footnote integrates seamlessly with the overall design and readability of your visualization. Careful application of these parameters guarantees that even supplementary text contributes positively to the interpretation of your data.

Conclusion: Enhancing Visualization Clarity

Adding a footnote or caption to a `ggplot2` plot is a critical step in producing professional, transparent, and reproducible data visualization. By relying on the dedicated `caption` argument within the `labs()` function, you ensure that the text is correctly formatted and positioned relative to the rest of the plot elements.

For default right alignment, the process requires only the addition of the `labs()` function. When custom alignment is necessary--such as left or center positioning--the `theme()` function, specifically targeting `plot.caption` using the `hjust` parameter within `element_text()`, provides the necessary control. Remember that `hjust=0` yields left alignment, `hjust=1` yields right alignment, and `hjust=0.5` centers the text.

The ability to precisely position and style supplementary text elevates the quality of your analytical outputs in R. Utilizing these simple yet powerful methods ensures that your viewers receive all necessary context without cluttering the primary visualization area, thereby maximizing the clarity and impact of your data story. We strongly encourage exploring other customization options within the `theme()` system to fully integrate footnotes into your unique aesthetic requirements.

The following tutorials explain how to perform other common tasks in `ggplot2`: